

Slave site table prefix

Posted by mokelly1 - 2012/03/06 11:54

I am writing a component that updates its tables with an Ajax routine. How do I find the table prefix for a site from the Ajax-php script. Is there a table that has site names and corresponding table prefix?

=====

Re: Slave site table prefix

Posted by edwin2win - 2012/03/07 18:38

If your Ajax perform a standard joomla initialization, the table prefix can be retrieve from the `$table_prefix = JFactory->getConfig("config.dbprefix");` or from the `$DB` connection.

If you do not perform a standard Joomla initialisation, you have to add it.

See the Joomla "index.php" file to get inspired of the initialisation.

The code depends on your joomla version (1.5 or 2.5).

In 2.5, the correct joomla initialization is

```
define('_JEXEC', 1);
define('DS', DIRECTORY_SEPARATOR);

if (file_exists(dirname(__FILE__) . '/defines.php')) {
    include_once dirname(__FILE__) . '/defines.php';
}

if (!defined('_JDEFINES')) {
    define('JPATH_BASE', dirname(__FILE__));
    require_once JPATH_BASE.'/includes/defines.php';
}
require_once JPATH_BASE.'/includes/framework.php';
```

You just have to change the path of the "site file" by the correct number of `dirname(dirname(....dirname(__FILE__)))` to retrieve the root directory of the site.

=====

Re: Slave site table prefix

Posted by mokelly1 - 2012/03/07 19:59

Does Multi Sites use a Joomla table to store information?

=====

Re: Slave site table prefix

Posted by edwin2win - 2012/03/08 18:59

NO.

JMS does not saves the website definition in the DB because it must be able to retrieve the information before providing to Joomla the path of the "configuration.php" file.

In fact, to have a quick decision, when you save a slave site definition, this generate PHP code that JMS execute to immediately take the decision of which website is called.

This is done to avoid consuming CPU and take a decision very quickly.

=====