

please clarify this

Posted by hassanali20 - 2009/08/05 12:58

In the com_multisites/models/manage.php after makeDB function

if error array is empty returning that array..

while creating slave site with new database, only database creating and tables are not created.

after comment the return \$error, tables created..

is that return statement kept purposely or any thing wrong from my side while installing component...

please clarify me.

```
// Duplicate the DB
if ( !empty( $fromSiteID) ) {
    // If duplicate in the same DB ?
    if ( ($toConfig->getValue( 'config.dbtype' ) == $fromConfig->getValue( 'config.dbtype'))
        && ($toConfig->getValue( 'config.host' ) == $fromConfig->getValue( 'config.host'))
        && ($toConfig->getValue( 'config.db' ) == $fromConfig->getValue( 'config.db'))
    )
    {} // Do nothing
    // Else try Create the "to DB" when it does not exists
    else {
        $errors = MultisitesDatabase::makeDB( $fromConfig, $toConfig);
        if ( empty( $errors ) ) {
            return $errors;
        }
    }

    // Connect on the "From" DB
    if ( $fromSiteID == ':master_db:') {
        $fromDB =& Jms2WinFactory::getMasterDBO();
    }
    else {
        $fromDB =& Jms2WinFactory::getSlaveDBO( $fromSiteID);
    }
}
else {
    $fromDB =& Jms2WinFactory::getMasterDBO();
}
```

Re:please clarify this

Posted by edwin2win - 2009/08/05 13:24

Which JMS release do you use.

It seems you are not using the RC5 that fix a bug in this routine.

See change history

<http://www.jms2win.com/faq/change-history-v12x>

The test is NOT empty

```
$errors = MultisitesDatabase::makeDB( $fromConfig, $toConfig);  
if ( !empty( $errors ) ) {  
    return $errors;  
}
```

I suggest that you get the latest version

See FAQ for procedure <http://www.jms2win.com/faq#sec-122>

<http://www.jms2win.com/get-latest-version>

Re:please clarify this

Posted by hassanali20 - 2009/08/07 10:09

Thanks,

we upgraded to new version.

one small help needed, is there any possibility to use different design (css) for different slave sites.

suppose i created 2 slave sites like slave1 and slave2, the components and modules are sharing from master site.If i want different design (layout and css) for master, slave1 and slave2. how can i achieve this.

Re:please clarify this

Posted by edwin2win - 2009/08/07 12:34

You just have to go in the admin of your slave site and select the default Joomla template that you want. Each slave site can select its own template.

If you want specific directory for the themes (template folder), this is also possible when you setup the slave site definition or JMS template themes folder.

See the user manual that give you the different possibilities depending on the platform.

Sometimes this is a copy and sometimes this is a Symbolic Link and sometimes this is a templates directory with Symbolic Links for each themes.

All depends on the platform and the value that you enter (or not) in the slave site definition (themes

folder field)

On Unix with Symbolic Link allowed, when you enter a value in the "themes folder", this create a templates directory in which each themes are initialy created as Symbolic Link.

In this case, the slave site can un-install the themes and re-install it to have its own copy rather than a link. The slave site can also install themes that are NOT present in the master website because it has its own templates directory.

=====