

## Code in .htaccess

Posted by doc\_in\_bc - 2010/02/13 06:02

---

Edwin. We have set up school district 82 (www.cmsd82.bc.ca) with sub domains for every school. Works wonders. However we have some schools with existing sites that they want to keep until their subscriptions run out. So we thought we'd just dummy up the school district site, and put a redirect to their existing site by putting the following in the .htaccess file for the school.

```
e.g. ##### Begin - Redirecting non-www request to www
#
RewriteEngine On
RewriteCond %{HTTP_HOST} ^roywilcox.cmsd82.bc.ca
RewriteRule (.*) http://www.roywilcoxschool.com/$1
#
##### End - Redirecting non-www request to www
```

However, changing one .htaccess file changes all - so in the end, we can only redirect one school. Is there a better way to do this?

Thanks, Edwin

Doug Thomson

---

## Re: Code in .htaccess

Posted by edwin2win - 2010/02/13 10:21

---

If you have deployed the slave site into a specific directory, you can have as many ".htaccess" than you have slave site.

So you just have to remove the Symbolic Link to the master and replace the specific file with a physical copy.

When you create the slave site, you can use a JMS templates where you specify that you want to copy the ".htaccess" instead of create a Symbolic Link that is the default.

You can do the same with the "robots.txt" if you decide to create additional directories in the slave site.

---

## Re: Code in .htaccess

Posted by doc\_in\_bc - 2010/02/14 01:43

---

So, am I to presume we simply delete the .htaccess (symbolic link) in each sub-domain folder and replace it with an .htaccess file that is a real file?

Thanks, again

Doug Thomson

Done! Works perfectly, many thanks.

=====